


T371000 Zenith TEXtiles®

Specification according to EN 1307

Identification	Standard	Data
Type of manufacture	ISO 2424	Tufting 1/10"
Aspect	ISO 2424	Cut pile
Pile fibre composition	ISO 2424	100% pa 6.6. Invista Antron Brilliance™
Dye method		Continue
Treatment		Teflon
Primary backing	ISO 2424	Polyester non woven
Backing	ISO 2424	TEXtiles®
Dimension	CEN/TS 14159	50 x 50 cm (20 tiles per box = 5 m ²)
Pattern report		-
Effective pile thickness	ISO 1766	Approx. 3,50 mm
Total thickness	ISO 1765	Approx. 8,00 mm
Total pile mass	ISO 2424	Approx. 1.000 g/m ²
Total mass	ISO 8543	Approx. 4.100 g/m ²
Number of tufts	ISO 1763	Approx. 220.000 /m ²
Effective pile mass	ISO 8543	-
Stroll test	ISO 6356	≤ 2 kV
Vertical resistance	ISO 10965	-
Horizontal resistance	ISO 10965	-
Classification for use	EN 1307	33 Commercial – heavy use
Luxury rating	EN 1307	LC3
Dimension Stability	EN 986	≤ 0,2 %
Impact sound reduction ΔL _w		Approx. 27 dB(A)
Sound absorption	EN ISO 354	-
Noise reduction	EN ISO 354	-
Thermal conductivity	ISO 8302	Approx. 0,07 m ² K/W
Flammability	EN 13501-1	B _{fl} – s1
ABZ-Nr.		Z-156.601-719



EN 14041:2004
12
0845-CPD-CX10141



Fletco Carpet Tiles products are to be installed in full accordance with our installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level.

Note: Fletco Carpet Tiles reserve the right to amend this specification without giving prior notice.

For the latest version of the technical specifications, check our internet site: www.fletco.com

Manufactured by:

Fletco Carpet Tiles A/S • Mads Clausensvej 2 • DK-7441 Bording • Tel.: +45 96 60 30 00 • Fax.: +45 96 60 30 60 • www.fletco.com